

SLIM-CASE

Slim design handheld enclosure

SLIM-CASE demonstrates what is possible with the design of a modern handheld enclosure, in terms of both appearance and function. The almost frameless design makes it possible to install low profile electronic components and assemblies as well as large displays and touchscreens of up to 4" (10 cm) into a compact device. Despite the small and handy dimensions, SLIM-CASE offers plenty of space inside for standard components such as PCBs, plug connectors, interfaces, sensors etc. Modern wireless data transfer/communication technology can also be accommodated in these slim innovative enclosures.

- Rounded sides and a flat compact design give the enclosure an extremely elegant look. They are also very comfortable to hold and allow functions that benefit from this design.
- The top part is available with three different operating panel designs to suit your individual control and display concept:

Flat operating panel

For easy arrangement of push buttons, displays, LEDs etc. Plus, printing of logos and legends.

Recessed (0.04") operating panel


Ideal for applications with product labels.

Recessed (0.06") operating panel

For fitting the transparent front screen or a membrane keypad.

- The transparent front screen (accessory) protects the displays underneath. It is rounded on the long edges to follow the contoured ergonomic shape of the case. Mounted with a double-sided adhesive film (accessory). On request, supplied individually printed from behind to match your visible display as well as masking the adhesive film.
- Suitable for fitting inductive charging with the correct coil, using NFC technology with Qi chargers. If required, internal power supply with a flat battery on the PCB.
- with and without TPE intermediate ring.
- protection class IP 54: SLIM-CASE vers. IV-VI with TPE intermediate ring;
protection class up to IP 65: SLIM-CASE vers. I-III with optional seal
- The TPE intermediate ring increases the installation height, serves as a sealing ring for IP54 protection class and provides impact protection. TPE in special colours, available on request.
- enclosure parts made of ASA+PC-FR (UL 94 V-0), off-white (RAL 9002)
- screw connection with stainless steel screws and Torx drive (T8)
- individual machining, e.g. cutouts for operating and display elements, interfaces, lettering, EMC aluminium vapour plating etc. on request

SLIM-CASE



Applications and Examples

Ideal for mobile electronics applications, indoors as well as outdoors. Measuring and control technology, wireless communication, IoT/IIoT, medical and laboratory technology, health care, office, safety engineering, environmental technology, etc.



Biofeedback to reduce stress



Remote control for interior design



Sensor Checkup System / Monitoring



Smart Home Control

View Customizing Options

What do you still need for your own very personal product? We can supply enclosures and tuning knobs with all necessary modifications for fitting your electronic components. Customizing options for Slim-Case

SLIM-CASE



Machining



Lacquering



Printing



Laser marking



Decor foils



RFI/EMI shielding



Installation / Assembly
of accessories

Select Versions



B5403107
SLIM-CASE M, Vers. I
ASA+PC (UL 94 V-0)
off-white RAL 9002
5.83"x2.91"x0.75"
IP 65 opt., IP 40



B5403117
SLIM-CASE M, Vers. IV
ASA+PC (UL 94 V-0)
off-white RAL 9002
5.83"x2.91"x0.87"
IP 54



B5403207
SLIM-CASE M, Vers. II
ASA+PC (UL 94 V-0)
off-white RAL 9002
5.83"x2.91"x0.75"
IP 65 opt., IP 40



B5403217
SLIM-CASE M, Vers. V
ASA+PC (UL 94 V-0)
off-white RAL 9002
5.83"x2.91"x0.87"
IP 54



B5403307
SLIM-CASE M, Vers. III
ASA+PC (UL 94 V-0)
off-white RAL 9002
5.83"x2.91"x0.75"
IP 65 opt., IP 40




B5403317
SLIM-CASE M, Vers. VI
ASA+PC (UL 94 V-0)
off-white RAL 9002
5.83"x2.91"x0.87"
IP 54



B5503201
Front screen M
PC
transparent
4.93"x2.50"x0.05"

SLIM-CASE

Accessory "protection"



B5503039
Seal M
Silicone
black



B5503201
Front screen M
PC
transparent
4.93"x2.50"x0.05"



B5503300
Adhesive foil M

Accessory "screws"



A0305031
Self-tapping screws 0.098" x
0.236" (PZ1)



A0325060
Self-tapping screw 0.098" x
0.236" (T8)
Stainless steel

Subject to technical modification without notice. © by OKW Gehäusesysteme, Buchen/Germany.